State Adoptions of the International Energy Conservation Code

State / District Click for Regulation	Model Code	Upcoming Amended Effective Date Adoption Date		Climate Zone(s)	Amendment Summary		
<u>Alabama</u>	2015 IECC	Х	10/1/2016		2,3	Attic hatch R-value has been reduced, equipment trade-offs have been added, and programmable thermostat requirement was removed. The maximum building leakage was relaxed to 5 ACH50 in CZ 2 & 3.	State Agency
<u>Alaska</u>	2018 IECC (Required by Alaska Housing Finance Corp.)	X	1/1/2019		7,8	Ceilling insulation was reduced in CZ 6 & 7 with energy-heel trusses. Continuous exterior insulation is not required. Insulation levels were increased for floors and slabs. Building leakage was relaxed to 4 ACH50.	State Agency
<u>Arizona</u>	No State Code				2,3,4,5	Four major jurisdictions have adopted the 2018 IECC. Chandler and Cave's Creek have adopted 2021 IECC with amendments.	SWEEP
<u>Arkansas</u>	2009 IECC	X	1/1/2015		3,4	Duct testing is optional. Relaxed CZ 4 window U-factor to .50. Ceiling R-value T1.1 (-)-15.8 (v62. (s)-45 (c)-9.9 (t))-45 7ing T /LiCl T /0iv15.8 (v(a)-9.FP AV	

State / District Click for Regulation	Model Code	Amended	Effective Date	Upcoming Adoption Date	Climate Zone(s)	Amendment Summary	Additional Code Links
<u>Hawaii</u>	2018 IECC	Х	12/15/2020		1	Sampling is allowed for single- and multi-family units. SHGC is dependent on overhang. Mass walls 6 in. or greater are exempted from R-Value requirements. Jalousie windows are exempted from requirements. Solar water heating is required for single-family. Trade-offs (Points Option) are allowed.	State Agency
<u>ldaho</u>	2018 IECC	Х	1/1/2021		5,6	CZ 5 fenestration and ceiling requirements were relaxed. Wood frame wall R-Value was relaxed for Zone 6. Sampling is allowed for single-family. Visual inspection for building tightness is allowed. Pipe insulation requirements were relaxed. High efficacy lighting was reduced to 75%. Special log home wall provisions were introduced.	State Agency
<u>Illinois</u>	2018 IECC	Х	7/1/2019		4,5	REScheck is allowed for compliance. No jurisdictions may adopt above-code requirements. Building tightness was relaxed to 4 ACH50. Sampling is allowed for low-rise multifamily. Basement insulation can extend to within 6 in. of the basement floor. Basement wall insulation was reduced. Restrictions on rooms with fuel-burning appliances were removed.	State Agency
<u>Indiana</u>	2018 IECC		12/26/2019		4,5	Energy conservation construction documents for 1- and 2-family homes only need to be submitted if required by the local jurisdiction. Fenestration, ceiling and wall values were relaxed. The building official may not require inspection by a third party. Verification through visual inspection is allowed.	State Agency
<u>Iowa</u>	2012 IECC	Х	6/1/2014		5,6	Wall R-values reduced from R-20+5 to R-20 in CZ 6. Relaxed maximum building leakage rate to 4 ACH50. Increased the allowable duct leakage from 4 to 6 cfm/100 sq ft. Panned duct returns allowed but must meet duct tightness requirements.	State Agency
<u>Kansas</u>	No State						

State / District Click for Regulation	Model Code	Amended	Effective Date	Upcoming Adoption Date	Climate Zone(s)	Amendment Summary	Additional Code Links
<u>Michigan</u>	2015 IECC	Х	9/20/2017		5,6,7	Ceiling and basement wall insulation was reduced for CZ 5. Wood frame wall values were reduced for CZ 6 & 7.	State Agency
<u>Minnesota</u>	2012 IECC	X	2/14/2015		6,7	Wall R-values were relaxed to remove continuous insulation requirement. Special basement insulation installation requirements were added. Ducts require a vapor retarder in some locations. Balanced mechanical ventilation is required.	State Agency
<u>Mississippi</u>	No State Code				2,3		State Agency
<u>Missouri</u>							

State / District Click for Regulation	Model Code	Amended	Effective Date	Upcoming Adoption Date	Climate Zone(s)
North Carolina	2015 IECC	Х	1/1/2019		3,4,5
<u>North Dakota</u>	2018 IECC	Х	1/1/2020		6,7

Relaxed the ACH50 to 5 or 0.30 CFM50/sq ft of surface area. Exempted duct systems smaller than 750 sq ft from being tested. Removed mechanical ventilation fan efficiencies. Relaxed SHGC to 0.30. Amended ceiling R-value to 38 or 30 ci.

Amendment Summary

State Agency

Additional

Code Links

State / District Click for Regulation	Model Code	Amendec	Effective Date	Upcoming Adoption Date	Climate Zone(s)	Amendment Summary	Additional Code Links
<u>Texas</u>	2015 IECC	X	9/1/2016		2,3,4	CZ 2 & 3, A 65 or lower score from September 1, 2016, to August 31, 2019, A 63 or lower score from September 1, 2019, to August 31, 2022, A 59 or lower score after September 1, 2022 CZ 4, A 69 or lower score from September 1, 2016, to August 31, 2019, A 67 or lower score from September 1, 2019, to August 31, 2022, A 63 or lower score after September 1, 2022. Several jurisidictions in Texas have gone through the adoption and amendment process for the 2021 IECC. The North Central Texas Council of Governments has created a set of amendment recommendations that several jurisdictions in Texas have elected to follow.	State Agency
<u>Utah</u>	2015 IECC	Х	7/1/2016			REScheck with 2006 IECC incorporated as optional compliance path, Building tightness relaxed to 5 ACH50, Duct tightness relaxed to 10 cfm/100 sq ft, Equipment tradeoffs incorporated into performance compliance, Alternate log home prescriptive path.	State Agency
<u>Vermont</u>	2015 IECC	х	9/1/2020		6		